

Round Bottom Tubes, 6 ml PS, with cap

APPLICATIONS:

Dilution of samples or solutions
Bacterial culture
Sample storage
Centrifugation of precipitates

FEATURES:

Polystyrene construction

- Optically clear for easy viewing of sample
- Hydrophobic, biologically inert surface for good cell / protein recovery.
- Stable from 4°C to 60°C
- Can withstand centrifugal forces up to 1400 rcf

Patented dual position snap cap

- Biologically inert polyethylene provides a chemically resistant surface.
- Loose position for sterile aerobic culturing.
- Tight closure for effective sealing.

Three sterile packaging options to suit customer's needs

- Available individually wrapped for optimal sterility (#352003)
- Can purchase 25/peel-open blister pack (#353058) or 125/bag (#352054)

STERILITY:

Product is gamma irradiated and dosimetrically based upon U.S. Association for the Advancement of Medical Instrumentation (AAMI) recommended practices in effect at the time of validation. Sterilization records are reviewed and signed off by qualified personnel for product release.

FDA COMPLIANCE:

FALCON products are manufactured in accordance with the current FDA Quality System Regulation (1996) as specified in Chapter 1, Title 21 of the code of USA Federal Regulations, Part 820 for medical devices.

RESTRICTIONS:

- Refer to Centrifuge Tube Chemical Resistance Chart, page 38 in the 1997 Becton Dickinson Labware catalog.
- Refer to "Thermoplastics Properties Chart," available via internet at <http://www.bd.com/labware/freestuf/>

Round Bottom Tubes, 6 ml PS, with cap

Material : Clear and Transparent Polystyrene

Related Catalog Numbers:

Cat. No.	Packout Description	Cap	Sterile	Graduations
352003	Ind. wrp'd, 500/Case	Dual	Yes	None
352054	125/Bag, 1000/Case	Dual	Yes	None
352058	25/Blister, 500/Case	Dual	Yes	None

Dimensions = mm(inches)

TUBE **A** = 75.54 (2.974)
 B = O.D. 12.40 (.488)
 C = O.D. 11.68 (.460)

Tube height w/cap = 76.22 (3.001)
 Top I.D. at rim = 10.72 (.422)
 Depth of rim = 3.05 (.120)
 Top I.D. at chamfer = 10.16 (.400)
 Bottom I. D. (Sph. Dia.) = 9.14 (.360)
 Min. wall thickness = .64 (.025) at the sides
 Nominal volume = 6mL
 RCF ratings = 1400 g's
 Chem. Compatibility: See Cat. Resistance Chart

CAP 12mm Snap Dual Position. Cat. #352032
 (Low Density Polyethylene)
E = 13.58 (.535)
D = O.D. 16.13 (.635)
 I.D. (bottom) = 13.26 (.522)

